5. PRODUCTION, IMPORT/EXPORT, USE, AND DISPOSAL

5.1 PRODUCTION

No information is available in the TRI database on facilities that manufacture or process tin or tin compounds because these chemicals are not required to be reported under Section 313 of the Emergency Planning and Community Right-to-Know Act (Title III of the Superfund Amendments and Reauthorization Act of 1986) (EPA 1997).

The earth's crust contains about 2–3 ppm tin, comprising 0.0006% of the earth's crust (Budavari 2001; Bulten and Meinema 1991). The most important tin containing mineral is cassiterite, SnO₂. Other tin minerals are stannite, teallite, cylindrite, and canfieldite. After tin-containing ores are mined, they undergo further separation processing resulting in concentrates containing 70–77% tin by weight, which is almost pure cassiterite, and are ready for smelting (Gaver 1997).

The world's largest producer of tin in 2003 was Indonesia (33% of the world total), followed by China (24%), Peru (19%), Bolivia (7%), Brazil (7%), and Australia (3%). Of the 20 countries that mine tin, these six account for 93% of the world total of 2.09×10^5 metric tons. Tin has not been mined in the United States since 1993. Production of tin stopped in 1989 at the only U.S. tin smelter at Texas City, Texas. However, the United States is believed to be the world's largest producer of secondary tin. In 2003, about 11,000 metric tons of tin from old and new scrap were recycled at 3 detinning plants and 70 secondary nonferrous-metal processing plants. The Defense Logistics Agency, which manages the National Defense Stockpile, sold 8,876 metric tons of pig tin from the stockpile in 2003. The Steel Recycling Institute stated that the steel can (tin-plated) recycling rate in the United States in 2003 was 60%. Tin is recovered, in addition to steel, in can recycling (Carlin 2003b, 2004). Production of organotin compounds was 5,000 tons in 1955 and approximately 35,000 tons in 1985 (Fent 1996). More recent production numbers for organotin compounds could not be located. Thirty one organotin compounds (e.g., bis(tributyltin) oxide, triphenyltin hydroxide, dibutyltin dichloride) are included on the U.S. High Production Volume (HPV) chemicals lists for 1990 and 1994. HPV chemicals are those that are manufactured in or imported into the United States in quantities ≥one million pounds per year (EPA 2004). Current U.S. manufacturers of selected tin compounds are given in Table 5-1.

Company Location Inorganic tin compounds Tin(II) chloride ATOFINA Chemicals, Inc. Specialty Chemicals Division Carrollton, Kentucky Tin(II) fluoride Ozark Fluorine Specialties, Inc. Tulsa, Oklahoma Tin(IV) oxide Engelhard Corporation, Appearance and Performance - Technologies Elyria, Ohio Ferro Corporation, Coatings, Colors, and Ceramics Group - Electronic Penn Yan, New York Materials Division Tin(II) fluoroborate Atotech USA Inc. Rock Hill, South Carolina **General Chemical Corporation** Claymont, Delaware OMG Fidelity, Inc. Newark, New Jersey Solvay Fluorides Inc. St. Louis, Missouri Methyltin compounds Dimethyltin dineodecanoate Tullytown, Pennsylvania Gelest, Inc. Tetramethyltin Clariant Life Science Molecules (America) Inc. Gainesville, Florida Tullytown, Pennsylvania Gelest. Inc. Butyltin compounds Dibutyltin acetylacetonate MacKenzie Company Bush, Louisiana Dibutyltin bis(2,4-pentanedionate) Tullytown, Pennsylvania Gelest, Inc. Dibutyltin bis(2-ethylhexanoate); Dibutyltin bis(isooctyl) maleate; Dibutyltin bis(isooctyl mercaptoacetate); Dibutyltin bis(isopropyl maleate); Dibutyltin bis(n-lauryl mercaptide); Dibutyltin dibutoxide; Dibutyltin dimethoxide; Dibutyltin disalicylate; Dibutyltin mercaptopropionate; Dibutyltin sulfide; Tributyltin fluoride ATOFINA Chemicals, Inc. Specialty Chemicals Division Carrollton, Kentucky Dibutyltin chloride; Dibutyltin oxide; Bis(tributyltin) oxide ATOFINA Chemicals, Inc. Specialty Chemicals Division Axis, Alabama; Carrollton, Kentucky Dibutyltin diacetate ATOFINA Chemicals, Inc. Specialty Chemicals Division Carrollton, Kentucky Ferro Corporation Performance and Fine Chemicals Group - Polymer Walton Hills, Ohio Additive Division Dibutyltin difluoride ATOFINA Chemicals, Inc. Specialty Chemicals Division Carrollton, Kentucky Rock Hill, South Carolina Atotech USA Inc.

Table 5-1. Current U.S. Manufacturers of Selected Tin Compounds^a

Company	Location
Dibutyltin dilaurate	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky
Ferro Corporation Performance and Fine Chemicals Group - Polymer Additives Division	Walton Hills, Ohio
Johnson Matthey, Inc. Alfa Aesar	Ward Hill, Massachusetts
Dibutyltin maleate	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky
Ferro Corporation Performance and Fine Chemicals Group - Polymer Additive Division	Walton Hill, Ohio
Tributyltin chloride	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Axis, Alabama; Carrollton, Kentucky
Tributyltin hydride	
Gelest, Inc.	Tullytown, Pennsylvania
Johnson Matthey, Inc. Alfa Aesar	Ward Hill, Massachusetts
Sigma-Aldrich Fine Chemicals	Plant location not specified
TetrabutyItin	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Axis, Alabama
Octyltin compounds	
Dioctyltin S,S'-bis(isooctylmercaptoacetate); Dioctyltin dichloride; Dioctyltin maleate	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky
Dioctyltin dilaurate	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky
Gelest, Inc.	Tullytown, Pennsylvania
Dioctyltin oxide	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky; Axis, Alabama
Tetraoctyltin	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Axis, Alabama
Phenyltin compounds	
Diphenyltin chloride; Diphenyltin oxide; Triphenyltin fluoride	
ATOFINA Chemicals, Inc. Specialty Chemicals Division	Carrollton, Kentucky

Table 5-1. Current U.S. Manufacturers of Selected Tin Compounds^a

^aDerived from SRI 2004. SRI reports production of chemicals produced in commercial quantities (defined as exceeding 5,000 pounds or \$10,000 in value annually) by the companies listed.

TIN AND TIN COMPOUNDS

5.2 IMPORT/EXPORT

U.S. consumption of primary and secondary tin was 34,000 and 5,830 metric tons, respectively, in 2002, and is estimated as 36,000 and 8,460 metric tons, respectively, for 2003. U.S. imports of refined tin in 2002 totaled 42,200 metric tons and were mainly from Peru, followed by China, Bolivia, Brazil, and Indonesia. Tin imports for 2003 are estimated at 37,000 metric tons. Major imports of tin include unwrought metal, waste and scrap, and unwrought tin alloys. Tin exports of refined tin were 2,940 metric tons in 2002, and are estimated at 4,020 metric tons for 2003 (Carlin 2004). U.S. imports for consumption of dibutyltin oxide, tetrabutyltin, and other organotin compounds were approximately 447, 611, and 2,070 metric tons, respectively in 2003, and were approximately 266, 649, and 1,680 metric tons, respectively, through August 2004 (ITA 2004).

5.3 USE

The major uses of tin in 2003 were: cans and containers, 27%; electrical, 23%; construction, 10%; transportation, 10%; and others 30% (Carlin 2004). Tinplate is used in food packaging, aerosol containers, and decorative applications. Various tin alloys are important, including bronze and pewter. Tin readily forms alloys with other metals and imparts hardness and strength. Tin is an important component of solders, since it wets the base metal by alloying with it (Gaver 1997).

Inorganic tin compounds are used in the glass industry, where they are added to strengthen the glass. Inorganic tin compounds also serve as the base for the formulation of colors, as catalysts, and in perfumes and soaps (WHO 1980). Tin(IV) oxide (SnO₂) is used in the ceramics and glass industries, as well as a polishing agent and as a catalyst (Kroschwitz and Howe-Grant 1997). It is also used to produce milky or colored glass and in the formulation of fingernail polish (Windholz 1983). Tin(IV) chloride (SnCl₄) is often used as the starting material for the production of organotin compounds. Tin(II) fluoride (SnF₂) is added to toothpastes as an anticaries agent. Tin(II) chloride (SnCl₂) is the most important inorganic tin compound. It is used as an industrial reducing agent and in tin electroplating. Tin(II) chloride is also used as a food additive, (e.g., as a preservative and a color-retention agent). Tin(II) fluoroborate (Sn(BF₄)₂), which is not isolated as a solid but is only found in solution, is an important chemical in electroplating. The consumption of inorganic tin compounds is lower than that of organotin compounds (Graf 1996; Kroschwitz and Howe-Grant 1997). TIN AND TIN COMPOUNDS

5. PRODUCTION, IMPORT/EXPORT, USE, AND DISPOSAL

Examples of commercially important organotin compounds include tetraorganotins (R₄Sn), triorganotins (R₃SnX), diorganotins (R₂SnX₂), and monoorganotins (RSnX₃). The organotin compounds of commercial importance have R groups equal to methyl, butyl, octyl, cyclohexyl, phenyl, or neophyl. The anionic X groups are commonly halides, oxide, hydroxide, carboxylates, or mercaptides. Tetraorganotin compounds are mainly used in the production of tri-, di-, and monoorganotin compounds. Tri- and diorganotin compounds are the most important classes of organotin compounds. Triorganotin compounds are used as industrial biocides, agricultural chemicals, wood preservatives, and marine antifouling agents. Diorganotin compounds are used as polyvinyl chloride (PVC) stabilizers and as polyurethane foam and esterification catalysts. Monoorganotin compounds are also used as PVC stabilizers, as well as in the treatment of glass (Batt 2004; Kroschwitz and Howe-Grant 1997).

The major commercial applications for which organotin compounds are used are as PVC heat stabilizers, biocides, catalysts, agrochemicals, and glass coatings, accounting for approximately 20,000 tons of tin consumption per year (Batt 2004). The major use of organotin compounds is for heat stabilization of PVC, which represents approximately two-thirds of the global consumption (Sadiki and Williams 1999). It was estimated that in 1981, the U.S. consumption of organotin compounds as PVC stabilizers was 10,650 tons, approximately 27% of the world market (Kroschwitz and Howe-Grant 1997). Organotin compounds used as PVC stabilizers include butyl-, octyl-, and methyltin compounds. Octyl- and methyltin compounds are used in PVC for food packaging. In the United States, the organotin compounds that are used predominantly as PVC stabilizers are methyltins (about 50% of the market) and butyltins (40%), with octyltin compounds making up the remainder. In Asia, methyltins (50%) and octyltins (40%) and in Europe, octyltins (60%) and butyltins (30%) are the most widely used organotin compounds as PVC stabilizers (Leaversuch 1999). Tributyltin compounds are also used as slimicides on masonry, as disinfectants, and as biocides for cooling systems, power station cooling towers, pulp and paper mills, breweries, leather processing, and textile mills (WHO 1990).

The use of triorganotin compounds as marine antifoulants has been restricted by the Organotin Antifouling Paints Control Act (June 16, 1988), which limits the type of vessel on which these paints can be used, and limits the use of tributyltin paints to those that have laboratory tested release rates of $\leq 4 \mu g/cm^2/day$ (Cardwell et al. 1999a). France was the first country to adopt restrictions in 1982, and now the majority of industrialized countries have adopted restrictions on the use of tributyltin containing paints on vessels <25 meters in length, and include, in addition to France and the United States, the United Kingdom, Canada, New Zealand, Australia, and the European Union (Birchenough et al. 2002). On October 5, 2001, the International Maritime Organization (IMO) adopted the International Convention

247

5. PRODUCTION, IMPORT/EXPORT, USE, AND DISPOSAL

on the Control of Harmful Anti-fouling Systems on Ships, which prohibits the use of harmful organotin compounds in anti-fouling paints on ships and established a mechanism to prevent the potential future use of other harmful substances as anti-fouling systems (IMO 2004).

5.4 DISPOSAL

Tin-containing wastes in the form of salts, slags, and muds are generated as a result of smelting, refining, and detinning processes. Solid wastes containing tin are generated by both domestic and industrial users of containers. Tin-containing wastes may be incinerated or disposed of in landfills (WHO 1980).

Inorganic and organic tin compounds may be disposed of in sealed containers in a secured sanitary landfill (NIOSH/OSHA 1981).

Tin is not listed as a hazardous waste constituent by the EPA and therefore, its disposal is not restricted by federal land disposal restrictions. No data were located regarding the amounts of tin disposed of by any means or trends in the disposal of tin.